

INSTALLATION ACCESSORIES

DRIVER BITS

TYPE PH-2, TX-20, TX-30



Code	Type	Lino size	Screw type
PH-S2-02110	PH-2	35, 55, 85	WDB, WSR
PH-S2-02160	PH-2	105, 135	WDB, WSR
PH-S2-02250	PH-2	155, 185	WDB, WSR
PH-S2-02350	PH-2	235, 285	WDB, WSR
TX-20S2-160	TX-20	35, 55, 85, 105, 135	WDB, WSR
TX-20S2-250	TX-20	155, 185	WDB, WSR
TX-20S2-350	TX-20	235, 285	WDB, WSR
TX-30S2-160	TX-30	35, 55, 85, 105, 135	WBSW
TX-30S2-250	TX-30	155, 185	WBSW
TX-30S2-350	TX-30	235, 285	WBSW

DRILL BITS FOR CONCRETE TYPE SDS - 5.0 mm

FOR WBSW AND WB6-C SCREWS



Code	Dimensions	Effective length [mm]
H-A782404	5.0 x 110	60
H-A782406	5.0 x 160	110
H-A782407	5.0 x 210	160
H-A782408	5.0 x 260	210
H-A782409	5.0 x 310	260

COUNTERSINK DRILL FOR DWS-500 EXTENSION - 5.0 MM

FOR WBSW AND WB6-C SCREWS



Code	Dimensions	Effective length [mm]
WSDP-05100	5.0 x 100	50

WSDP DRILL EXTENSION WITH WEDGE

FOR WSDP-05100 DRILL



Code	Effective length [mm]
DWS-500	500