

## PMWWS-750 (4 SEASONS FORMULA)

### STRAW FOAM MULTI



- excellent foam texture
- good adhesion
- high yield
- short curing time
- good price/quality ratio



Technical Approval  
AT-15-9422/2014

### TECHNICAL DATA

Code	Can size	Quantity per box
PMWWS-750	750 ml	12

### APPLICATION:

MULTI is a one-component fixing and sealing foam that guarantees high yield, excellent adhesion and a short curing time. Its 4 seasons formula is suitable for application temperatures from -10°C to +30°C and its excellent mechanical properties will satisfy even most demanding users.

Polyurethane foam MULTI is suitable for sealing voids when mounting door and window frames, for sound insulation of walls and filling holes and entries through walls. It can be used as an aid to fixing of shower trays and bath tubs. Suitable for mounting of window sills and roller blind casings while ensuring high heat and sound protection.

## PMPWS-750 (4 SEASONS FORMULA)

### GUN FOAM MULTI



- INNOVATIVE APPLICATOR**
- included with MULTI Gun Foam
  - ENSURE BEST RESULTS
  - EVEN WITHOUT standard foam gun**
  - cost-effective and accurate dosing
  - high-quality foam texture
  - applicator included for free!

- excellent foam texture
- good adhesion
- high yield
- short curing time
- good price/quality ratio



Technical Approval  
AT-15-9422/2014

### TECHNICAL DATA

Code	Can size	Quantity per box
PMPWS-750	750 ml	12

### APPLICATION:

MULTI is a one-component fixing and sealing foam that guarantees high yield, excellent adhesion and a short curing time. Its 4 seasons formula is suitable for application temperatures from -5°C to +30°C and its excellent mechanical properties will satisfy even most demanding users.

Polyurethane foam MULTI is suitable for sealing voids when mounting door and window frames, for sound insulation of walls and filling holes and entries through walls. It can be used as an aid to fixing of shower trays and bath tubs. Suitable for mounting of window sills and roller blind casings while ensuring high heat and sound protection.