

KW Narrow angle bracket





AT-15-8508/2012



Description

Three-dimensional plate fasteners for nailing are used for timber-to-timber connections. Can be made with the following fasteners: nails, screws, ring shank nails and screws. Material: steel sheet. Corrosion protection: zinc plated. Fire resistance class A1





Code	Dimensions [mm]				No. of holes		Design resistance [kN]	Pcs
	A	B	C	D	ø4.5	ø6.0		
KW-01(X100)	25	25	15	2	4	-	0.73	100
KW-02(X100)	30	30	15	2	4	-	0.73	100
KW-03(X100)	40	40	15	2	4	-	0.73	100
KW-04(X100)	50	50	15	2	4	-	0.73	100
KW-05(X100)	60	60	15	2	4	-	0.73	100
KW-06(X100)	75	75	15	2	4	-	0.73	100
KW-07(X100)	90	90	20	2	4	-	0.73	100
KW-08(X50)	100	100	20	2	4	-	0.73	50
KW-09(X50)	100	100	20	4	4	-	0.73	50
KW-10(X50)	120	120	20	2	4	-	0.73	50
KW-11(X50)	125	125	20	5	-	4	0.73	50
KW-12(X50)	150	150	25	5	-	4	0.73	50

KS Wide angle bracket



AT-15-8508/2012



Code	Dimensions [mm]				No. of holes		Design resistance [kN]	Pcs
	A	B	C	D	ø4.5	ø6.0		
KS-01(X100)	30	30	30	2	4	-	1.13	100
KS-02(X100)	40	40	40	2	4	-	1.13	100
KS-03(X50)	60	60	60	2	4	-	2.14	50
KS-04(X50)	75	40	25	2	-	5	2.14	50

Description

Three-dimensional plate fasteners for nailing are used for timber-to-timber connections. Can be made with the following fasteners: nails, screws, ring shank nails and screws. Material: steel sheet. Corrosion protection: zinc plated. Fire resistance class A1