

PMPPLE-750
PMPZLE-750 WINTER FORMULA
GUN FOAM PROFESSIONAL LOW EXPANSION



PMPZLE-750
WINTER FORMULA -10°C

- very low expansion rate
- excellent foam texture
- good adhesion
- high yield
- short curing time



Technical Approval
AT-15-9422/2014

PMPL-900-65L
PMPZ-900-65L WINTER FORMULA
GUN FOAM PROFESSIONAL 65



INNOVATIVE APPLICATOR

- included with GUN FOAM PROFESSIONAL 65 ENSURE BEST RESULTS
- EVEN WITHOUT standard foam gun
- cost-effective and accurate dosing
- high-quality foam texture
- applicator included for free!



PMPZ-900-65L
WINTER FORMULA -10°C

- high yield up to 65 l per 1000 ml
- excellent foam texture
- good adhesion
- short curing time



Technical Approval
AT-15-9422/2014

TECHNICAL DATA

Code	Can size	Quantity per box
PMPPLE-750	750 ml	12
PMPZLE-750 (winter formula)	750 ml	12

APPLICATION:

PROFESSIONAL LOW EXPANSION is a one-component fixing and sealing foam that has a low expansion formula and guarantees good thermal and acoustic insulation, excellent adhesion to all substrates and a short curing time. Winter formula (PMPZLE-750) offers excellent properties and application temperatures from -10°C to +30°C. Polyurethane foam PROFESSIONAL LOW EXPANSION is suitable for sealing voids when mounting door and window frames. Due to low expansion properties it is highly recommended for gap filling when mounting thin-profile PVC frames, thin aluminum profiles, window sills, stairs and roller blind casings. It offers a very good sound insulation of partition walls in drywall systems, ensures thermal and acoustic insulation of attics, floor and air-conditioning systems. It can be used for fixing and soundproofing of shower trays and baths, filling pipe and cable entries, and sealing connection joints in the wall and ceiling area.

TECHNICAL DATA

Code	Can size	Quantity per box
PMPL-900-65L	900 ml	12
PMPZ-900-65L (winter formula)	900 ml	12

APPLICATION:

PROFESSIONAL 65 is a one-component multi-purpose foam sealant. Its perfect formula ensures high yield (65 l per 1000 ml), outstanding mechanical properties, good adhesion to all building materials, and a short curing time will satisfy even most demanding users.

Winter formula (PMPZ-900-65L) guarantees good adhesion, short curing time and application temperatures between -10°C and +30°C.

The applicator gun will guarantee superior dispensing control, maximise the yield and make application more convenient. Polyurethane foam PROFESSIONAL 65 is suitable for sealing voids in mounting door and window frames, sound insulation of walls and filling holes and entries through walls. It can be used as an aid to fixing shower trays and baths. Suitable for mounting of window sills and roller blind casings while ensuring high heat and sound protection.