

ZUA - 310

Winter acrylic sealant - white



Description

Universal permanently plasto-elastic one-component sealant based on acrylic dispersions. Used for filling of external and internal cracks, seams and crevices prior to painting. Not recommended for areas subject to frequent water contact.

Filling of cracks and crevices in walls and ceilings. Suitable for finishing of interior corners in drywall systems and filling of gaps between door frames and walls. Use for elastic joining of walls and ceilings with decorative elements as well as sealing of window and door frames.

EN-Short-term frost resistance - maximum of 10 days in temperature down to -18°C. Resistant to freeze/thaw in 7 cycles at temperatures between -18 and +23°C where a cycle lasts 48 hours (24 hours at -18°C and 24 hours at +23°C).

Code	Colour	Cartridge size	Pcs. 
ZUA-310-BI(X12)	White	310 ml	12

UAL - 300

Light acrylic filler



Description

Ready to use acrylic material for filling of drywall seams, gaps and cracks in internal walls. Excellent adhesion to most substrates, solvent-free formula and easy sanding and painting make it a universal multi-purpose product with a wide range of applications.

Suitable for filling of drywall seams, cracks and crevices in internal walls, re-pairing of bad drywall seams, masking of screw heads and other fasteners, filling of movement joints (including those between woodwork and walls), working with corning and coving as well as plaster and polystyrene decorations.

Code	Colour	Cartridge size	Pcs. 
UAL-300(X15)	White	300 ml	15