

UWT-310

HIGH TEMPERATURE SEALANT



TECHNICAL DATA

Code	Colour	Can size	Quantity per box
UWT-310-CZ	Black	310 ml	12

APPLICATION:

T1500 (°C) High Temperature Sealant is a fire-resisting sodium silicate based paste for filling and fixing cracks and fissures and also for putting in chimneys, ovens, barbecues, fireplaces, smoke-houses, etc. Not suitable for sealing places where flexible bond is required (central heating, gas system). Not to be used in applications where contact with food is required.

Weatherproof and UV resistant when cured. Not waterproof. Does not contain asbestos. **Fire resistance when cured +1500°C**

SSN-310

SANITARY SILICONE SEALANT - WHITE



TECHNICAL DATA

Code	Colour	Can size	Quantity per box
SSN-310-BI	White	310 ml	12

APPLICATION:

Universal permanently elastic one-component neutral curing silicone sealant which offers excellent adhesion to porous and non-porous substrates and is suitable for a range of external and internal applications. This silicone sealant is resistant to UV radiation. Fungicide additives make it insensitive to long-lasting damp and resistant to fungi and mildew.

Elastic sealing of different building and finishing materials; sealing of window frames, shop-windows and glass cases. Suitable for use in sanitary applications, washrooms, etc. Suitable for installation of sanitary ware including baths, wash basins, shower trays. Suitable for use on a variety of substrates including metal, acrylics, stone, wall, brick, cement, wood, aluminium, glass and glazed surfaces, and also PVC. Do not use for sealing aquariums.